



Specifications Sylvania LED Downlight Start 205 Aluminium White 20W
2150lm 77D - 840 Cool White | Cutout 205mm - IP54

[View Product](#)

General Information

| | |
|--------------------------|----------------------------|
| SKU | 255264 |
| EAN | 5410288303291 |
| Brand | Sylvania |
| Manufacturer Name | ST DWNLT 205 IP54 2150 840 |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 2x18 |
| Wattage | 20 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |

| | |
|--------------------------|------------------------------------|
| Beam Angle (degree) | 77 |
| Luminous Flux (Lumen) | 2150 |
| Luminous Efficacy (lm/W) | 107.5 |
| Power factor | >0.90 |
| Unified Glare Rating | < 25 - for hallways and staircases |
| Optical Cover | Opal |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Recessed |
| IP-rating | IP54 |
| Impact Protection (IK) | IK07 - 2 joules |
| Operating Temperature | -10 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Fixture Connection | PI [Push-in connector] |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 60 |
| Diameter (mm) | 220 |

Sensor Information

Type of sensor

Why Any-lamp?
No Sensor

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process