



Specifications Philips LED Downlight GreenSpace2 DN461B 9.8W 1050lm 120D - 830 Warm White | 166mm - Aluminium Reflector - Emergency 3H

[View Product](#)

General Information

| | |
|--------------------------|-------------------------------------|
| SKU | 235959 |
| EAN | 8718699793432 |
| Brand | Philips |
| Manufacturer Name | DN461B LED11S/830 PSE-E C ELP3 WH P |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |

Technical Information

| | |
|-----------------------------|---------------------|
| Emergency Lighting | With Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Wattage | 9.8 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 120 |
| Luminous Flux (Lumen) | 1050 |
| Luminous Efficacy (lm/W) | 107 |

| | |
|-------------------------|--------------------------------|
| Power factor | >0.90 |
| Installation Depth (mm) | 77 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Finish of Reflector | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|--------------------|
| EOC8 | 79343200 |
| Mounting Method | Recessed |
| Cut out (mm) | 150 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | +10 to +40 |
| Housing | PC (Polycarbonate) |
| Colour of the Fixture | White |
| Colour of material | White |
| Series | DN461B |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 77 |
| Diameter (mm) | 166 |

Why Any-lamp?

Sensor Information

 Order from the **largest lighting specialist** in Europe  **Customised** quotation
Type of sensor No Sensor

 **Up to 7 years warranty**  **Easy return process**