



Specifications Noxion LED Panel  
Louvre Excell Pronox 34W 3800lm -  
840 Cool White | 60x60cm - UGR 152 -  
Dali Dimmable

[View Product](#)

## General Information

|                          |   |
|--------------------------|---|
| SKU                      | 235759  |
| EAN                      | 8719157006514   |
| Brand                    | Noxion  |
| Manufacturer Name        | Noxion LED Louvre Excell G2. 34W 4000K 600 Polish DALI (4x14W eqv.) |
| Any Lamp all-in warranty | 6 Years   |
| Average Lifetime (h)     | 70000   |
| Series                   | Louvre Excell   |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 34                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 3800               |

|                          |   |
|--------------------------|---|
| Luminous Efficacy (lm/W) | 111.8                                   |
| Suitable for Outdoor     | No                                      |
| IP-rating                | IP20                                    |
| Impact Protection (IK)   | IK02 - 0.20 joule                       |
| Fixture Connection       | Terminal, 2-pole (MAINS)   2-pole (DIM) |
| Finish of Reflector      | Gloss                                   |
| Driver Included          | Yes                                     |
| Power factor             | >0.90                                   |
| Product Type Category    | LED Panel                               |

## Fixture Information

---

|                       |                                  |
|-----------------------|----------------------------------|
| Mounting Method       | Recessed                         |
| Unified Glare Rating  | < 15 - for special applications  |
| Optical Cover         | PET (Polyethylene Terephthalate) |
| Operating Temperature | -20 to +50                       |
| Emergency Lighting    | No Emergency Unit                |
| Colour of the Fixture | White                            |
| Housing               | Steel                            |
| Colour of material    | White                            |

## Dimensions

---

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 55      |

## Sensor Information

---

Type of sensor

No Sensor

### Why Any-lamp?

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process

